

INPUT

+20dB
 Instr.

Bright
 Instr.

GAIN (dB)
 30
 20
 10
 0
 40
 50
 60
 Line
 Input Select

48V
 Mic
 100Hz
 H.P.

Ø Rev
 100Hz
 H.P.

Clip
 0
 -10
 -30
 dB

DYNAMICS

GATE

-20
 -40
 -60
 +20 dB
 Off
 Threshold

Rel.
 Slow

DE-ESS

3
 4
 5
 6
 7
 8
 9
 10
 Off

Female
 Male

COMPRESSOR

-10
 0
 +10
 -20
 -30
 +20 dB
 Threshold

3
 2
 1.5
 1.2
 ∞
 :1
 Ratio
 20
 10
 5
 1
 GR

-10
 0
 +10
 -20
 +20 dB
 Gain
 Dyn.
 In.

EQUALISER

LF

 -6
 0
 +6
 -12
 +12
 -18
 +18
 dB
 Cut/Boost

MID PARAMETRIC

500
 1K
 2K
 4K
 8K
 150
 Hz
 16K
 Frequency

1
 2
 3
 .3
 Bandwidth

-6
 0
 +6
 -12
 +12
 -18
 +18
 dB
 Cut/Boost

HF

 -6
 0
 +6
 -12
 +12
 -18
 +18
 dB
 Cut/Boost

Eq
 In.

TUBESOUND

Lo

 4
 7
 0
 11
 Drive

Mid

 4
 7
 0
 11
 Drive

Hi

 4
 7
 0
 11
 Drive

In.

OUTPUT

Pre-Fade
 Limiter
 Soft
 Hard

Master Fader (dB)

 -5
 0
 +5
 -10
 +10
 -20
 +15
 ∞

-20
 -15
 -10
 -5
 0
 +5
 +10
 +15

In.

DRAWMER

MX60

FRONT END *One*

DRAWMER MX60 Session Recall

DRAWMER ELECTRONICS LTD ~ Coleman Street
Rotherham ~ S. Yorkshire ~ UK

© COPYRIGHT DRAWMER ELECTRONICS LTD 2021

Session No.	
Date	
Artist	
Tape Location	