

INPUT

+20dB Instr. Line H.P.
 Bright 48V Mic 100Hz
 30 40 50 60 dB
 ^ Clip Rev 0 -10 -30 dB

In. Input Select

GATE

Off Rel. Slow
 Threshold -20 -40 -60 -80 -20 dB

DE-ESS

Off Male Female
 1 2 3 4 5 6 7 8 9 10

COMPRESSOR

20 10 5 3 2 1.5 1.2 1 1.1
 Threshold -20 -30 -40 -10 -20 dB Ratio

GR 5 10 20 30 40 50 60 70 80 90 100 dB Dyn. Gain

EQUALISER

LF MID PARAMETRIC HF
 -12 -6 0 +6 -6 0 +6 -6 +6 -12 +12 -18 +18 -12 +18 -18 +18 dB Cut/Boost In.

1K 2K 5K 10K 150 Hz 1K 8K
 Frequency Bandwidth Cut/Boost

TUBESOUND

Lo Mid Hi
 Drive Drive Drive
 0 11 0 11 0 11 0 11 0 11

OUTPUT

Pre-Fade Limiter Soft Hard Master Fader (dB)
 -20 -15 -10 -5 0 +5 +10 +15 -5 0 +5 +10 +15

DRAWMER MX60 FRONT END *One*

<h1 style="margin: 0;">DRAWMER MX60 Session Recall</h1> <p style="margin: 5px 0;">DRAWMER ELECTRONICS LTD ~ Coleman Street Rotherham ~ S. Yorkshire ~ UK</p> <p style="margin: 5px 0; font-size: small;">© COPYRIGHT DRAWMER ELECTRONICS LTD 2011</p>	Session No.
	Date
	Artist
	Tape Location